

DigiLED



Dip Switch - SW1

1	2	3	4
0	0	0	0 - O ₂
1	0	0	0 - O ₃ [%]
0	1	0	0 - O ₃ [g/m ³]
0	0	1	0 -Flow [LPM]
0	0	0	1 T - O ₂ [°C]
1	0	0	1 T - O ₃ [°C]

1 - On , 0 - Off

An accessory to DigiO3, this display provides a user with the ability to display the DigiO3 measurements in bright different colors: Blue, Green & Red. Connection is accomplished via an ordinary 4 wire telephone (or other) cable , which delivers power and RS-232 bit stream from the DigiO3 to DigiLED. No dedicated external power supply is necessary - DigiLED receives its power supply from DigiO3 power source.

Specification:

Size	3.5" x 2"
Segment size	0.8"
Colors	Blue, Green, Red
RS-232 IN	Is received from the DigiO3
RS-232 OUT	Continues to other DigiLED's, thus only one DigiO3 connection is needed
Weight	15g
Power	8-15V / 90ma
P/N	DigiLED-Blue; DigiLED-Green; DigiLED- Red

RJ11 Connectors

<u>J1 - RS-232 IN</u>		<u>J2 - RS-232 OUT</u>	
<u>Pin</u>	<u>Function</u>	<u>Pin</u>	<u>Function</u>
1	DC in	1	GND
3	RXD	2	TXD
4	GND	4	DC out